

SAFETY DATA SHEET

Section 1 – Product & Company Identification

Product Name:
Rechargeable Advanced Lithium Ion Batteries

P/N Cells:
US18650VTC4

Product Catalog No.:
43323, 43328, 44693, 44698, 44848, 44853, 48483

Recommended Use:
RIDGID Press Tools

Company Information:

North America

Ridge Tool Company
400 Clark Street
Elyria, Ohio 44035-6001
1-800-519-3456
(8:00 am – 5:00 pm EST, M-F)
Emergency Telephone
call 9-1-1 or local emergency number
www.RIDGID.com

Australia

Ridge Tool Australia
127 Metrolink Circuit
Campbellfield, VIC 3061
1-800-743-443
(8:30 am – 5:00 pm AEST, M-F)
Emergency Telephone
call 000 or local emergency number
www.RIDGID.com.au

Issue Date: March 3, 2017

Section 2 – Hazards Identification

This product is defined as an article per US OSHA 29CFR 1910.1200 (HazCom 2012).

GHS Label Elements: Not applicable

The materials in these Li-Ion batteries are hermetically sealed in a case and do not leak electrolyte under normal usage conditions. However, if exposed to a fire, explosion, extreme abuse, misuse or improper disposal that results in breaching of the battery cell case, hazardous materials may be released. Also, battery terminal contact with other metals may generate heat or cause electrolyte leakage. Electrolyte is flammable. Direct contact with electrolyte may cause severe irritation and chemical burns. Short-term skin exposure may cause chemical burns and sores. Inhalation and injection are not anticipated routes of exposure with leakage of small amounts of electrolyte.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 3 – Composition / Information On Ingredients

Composition:

- Cathode: Lithium nickel cobalt manganese oxides (active material)
Polyvinylidene fluoride (binder)
Graphite (conductive material)
- Anode: Graphite (active material)
Polyvinylidene fluoride (binder)
- Electrolyte: Organic solvent (non-aqueous liquid)
Lithium salt

Does not contain heavy metals such as mercury, cadmium, lead or chromium

Average Operating Voltage (V)	Rated Capacity	Nominal Capacity
3.6	2000mAh (7.2 Wh)	2100mAh (7.6 Wh)

Section 4 – First Aid Measures

EYE CONTACT:

If contents from an opened battery encounters the eyes, immediately flush eyes thoroughly with water and continue flushing for at least 15 minutes without rubbing. Seek medical attention.

SKIN CONTACT:

If the contents from an opened battery comes in contact with the skin, wash with soap and water. If irritation persists or contact has been prolonged, seek medical attention.

INHALATION:

If exposure to fumes or dusts occurs, remove immediately to fresh air and seek medical attention.

INGESTION:

If contents from an opened battery are swallowed, do not induce vomiting. Seek medical attention immediately.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 5 – Fire Fighting Measures

In case of fire use CO₂ or CLASS D fire extinguisher.

In case battery burns with other combustible, use corresponding fire extinguisher. Corrosive fumes may be present during fire. Use protective equipment (gloves, breathing apparatus, goggles etc.)

Gases from the burning fire will include Hydrogen Fluoride, Carbon oxides, Hydrocarbons among others.

Section 6 – Accidental Release Measures

PERSONAL PRECAUTIONS:

Use rubber gloves and safety glasses, and a gas mask for organic gases when handling leaking battery. Move batteries and contents away from open fire.

ENVIRONMENTAL:

No additional information.

CLEAN-UP MEASURES:

Spills and leaks are unlikely because cells are contained in a hermetically sealed case. If the battery case is breached, wear protective clothing that is impervious to caustic materials and absorb or pack spill residues in inert material.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 7 – Handling And Storage

HANDLING:

Accidental short circuit (contacting positive and negative battery terminals with a conductive object) will bring high temperature evaluation to the battery as well as shorter battery life. Be sure to avoid prolonged short circuit since the heat can burn attendant skin and can even rupture the battery cell case. Batteries placed in bulk containers should not be shaken. Metallic objects in tool boxes can cause short circuit. Do not disassemble, remodel, or solder.

CHARGING:

This battery is designed for recharging. Charge battery before use. Observe the specified charging instructions since incorrect charging can cause a rise in internal gas pressure which may result in damaging heat generation or cell rupture and/or venting.

STORAGE:

Store in a cool, well-ventilated location. Prevent condensation on cell or battery terminals. Store within the recommended temperature range of -4°F (-20°C) and 113°F (45°C). Do not expose to temperature above 140°F (60°C). Avoid exposure to static electricity so that no damage will be caused to the protective circuitry of the battery pack. Do not store with metal jewelry, metal covered tables, or metal belts.

CAUTION: Do not dispose in fire, mix with other battery types, charge above specified rate, connect improperly, or short circuit, which may result in overheating, explosion, or leakage of cell contents.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 8 – Exposure Controls / Personal Protection

EXPOSURE GUIDELINES:

Not specified

ENGINEERING CONTROLS:

None required under conditions of normal use. Provide appropriate ventilation in case of electrolyte leakage or exposure.

PERSONAL PROTECTIVE EQUIPMENT:

- **Eye Protection**
None required under conditions of normal use, safety goggles in case of electrolyte leakage.
- **Skin Protection**
None required under conditions of normal use, safety gloves in case of electrolyte leakage.
- **Respiratory Protection**
None required under conditions of normal use, gas mask in case of electrolyte leakage.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 9 – Physical And Chemical Properties

Appearance

Physical State

Form

Color

Odor

Odor Threshold

pH

Melting point/freezing point

Initial boiling point and boiling range

Flash point

Evaporation rate

Flammability (solid, gas)

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%)

Flammability limit - lower (%)

Explosive limit – upper (%)

Explosive limit – lower (%)

Vapor pressure

Vapor density

Relative density

Solubility(ies)

Solubility in water

Solubility (other)

Partition coefficient (n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Sealed Battery

Mostly cylindrical

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

No data available

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 10 – Stability And Reactivity

STABILITY:

Since batteries utilize a chemical reaction they are considered a chemical product. As such, battery performance will deteriorate over time, even if stored for a long period of time without being used. In addition, if the various usage conditions such as charge, discharge, ambient temperature, etc. are not maintained within the specified ranges the life expectancy of the battery may be shortened or the device in which the battery is used may be damaged by electrolyte leakage. The battery is stable under normal operating conditions.

CONDITIONS TO AVOID:

Open flames, heat, sparks and moisture. Battery should not be incinerated, crushed, or abused. Do not subject battery to temperatures in excess of 140°F (60°C).

INCOMPATIBLE MATERIALS:

No additional information known.

DECOMPOSITION PRODUCTS MAY INCLUDE:

No additional information known.

POSSIBILITY OF HAZARDOUS REACTIONS:

No additional information known

Section 11 – Toxicological Information

ACUTE TOXICITY: No further toxicological data known.

CHRONIC: No further toxicological data known.

SENSITIZATION: No further toxicological data known.

REPRODUCTIVE EFFECTS: No further toxicological data known.

TERATOGENIC EFFECTS: No further toxicological data known.

MUTAGENICITY: No further toxicological data known.

SYNERGISTIC MATERIALS: No further toxicological data known.

CARCINOGENICITY: No further toxicological data known.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 12 – Ecological Information

ECOLOGICAL INFORMATION:

No information available.

Section 13 – Disposal Consideration

WASTE DISPOSAL:

Li-Ion batteries should not be incinerated or subjected to temperatures in excess of 140°F (60°C). Such treatment can cause cell rupture. In the event of disposal, dispose only in accordance with federal, state and local regulations.

These Li-Ion batteries are classified as hazardous waste and are not safe for disposal in the normal waste stream. The Ridge Tool Company encourages recycling, as these batteries do contain recyclable materials that can be reused. The battery packs bear the Rechargeable Battery Recycling Corporation (RBRC) symbol, indicating RIDGID has already paid the cost of recycling the lithium-ion battery packs once they have reached the end of their useful life. For recycling center locations, call 1-800-822-8837.

Section 14 – Transportation Information

UN Number: 3480

Proper Shipping Name: Lithium Ion Batteries

This battery is less than 100WH and has successfully passed UN safety testing. Batteries are packaged in a manner that prevents short circuits and other damage that could lead to failure.

Regulations governing dangerous goods will be relevant when transporting batteries. Follow applicable laws and regulations for transport and disposal.

Special procedures must be followed in the event batteries are damaged, including inspection and repacking. Damaged or defective batteries must not be transported by air.

Product Name.....: Rechargeable Advanced Lithium Ion Batteries

Section 15 – Regulatory Information

Check with the appropriate regulatory agencies as regulations may have quantity restrictions, operator variations, or other special provisions

Section 16 – Other Information

Prepared by: Ridge Tool Company (Operating Standard 6-416)

Issue Date: 3 March 2017

Last Revision Date: 19 May 2016

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.