

Inspection Camera System

The SeeSnake® nanoReel opens up new possibilities in long run small-diameter inspection jobs. Applications where only bore scopes could reach can now be inspected using the nanoReel. Boiler Tubes, Supply Lines, Sprinkler Systems and a wide array of specialty applications can all be inspected using the nanoReel.



- **Small Diameter and Tight-Turn Radius** camera allows 1" lines up to 85 feet to be inspected.
- **Lightweight and Compact** unit allows for easy transport and efficient storage.
- **Multiple Monitor Compatibility** allows you to use the nanoReel with your existing SeeSnake monitor or the micro CA-300 and microEXPLORER™ Digital Inspection Cameras.
- **Interchangeable Drums** let you change out the inner drum depending on the application. Choose from:
 - **L100/L100C** - 1½' to 4" lines with a stiffer push cable allowing you to inspect lines up to 100 feet.
 - **D30 and D65S** - Small diameter with tight turns, 1½' to 3" P-Traps, toilet traps, pool lines up to 65 feet.
 - **N85S** - Ultra small diameter lines 1" to 2" with tight turns for specialized applications.

SPECIFICATIONS

Camera Head	0.62" (15.5mm)
Cable Length	85' (25m)
Cable Diameter	0.25" (6.3mm)
Line Capacity	1" to 2"
	(19 - 50mm)
Weight	9.5 lbs. (4.1 kg)
Length	13.25" (33.7cm)
Width	6.6" (16.8cm)
Height	17.5" (44.5cm)
Resolution	510 x 496 NTSC
Sonde	512Hz

ORDER INFORMATION

CATALOG NO.	DESCRIPTION
40013	nanoReel N85S Inspection Camera
40003	nanoReel N85S Inspection Camera – CA350
40448	nanoReel N85S Drum Only



For a FREE DEMONSTRATION*
 contact your **RIDGID representative**
 *Selected products only & subject to availability & location





SPECIFICATIONS

	nanoReel N85C	microDrain D65S	microReel L100C
Camera Head	0.62" (15.5mm)	0.86" (22mm)	0.98" (25mm)
Cable Length	85' (25m)	30' (10m) / 65' (20m)	100' (30m)
Cable Diameter	0.25" (6.3mm)	0.33" (8.3mm) flexible	0.27" (6.7mm) stiff
Line Capacity	1" to 2" (19 - 50mm)	1" to 3" (25 - 76mm)	1.5" to 4" (38 - 100mm)
Weight	9.5lbs. (4.1 kg)	8.6 lbs. (3.9 kg) / 9.8 lbs. (4.4 kg)	10.3 lbs. (4.7 kg)
Length	13.25" (33.7 cm)	13.25" (33.7 cm)	13.25" (33.7 cm)
Width	6.6" (16.8 cm)	6.6" (16.8 cm)	6.6" (16.8 cm)
Height	17.5" (44.5 cm)	17.5" (44.5 cm)	17.5" (44.5 cm)
Resolution	510 x 496 NTSC	510 x 496 NTSC	510 x 496 NTSC
Ball Guide	2 included	2 included	2 included
Sonde	512Hz	Optional 512Hz	512Hz
Counter	NA	NA	Optional
Applications	Boiler Tube Inspection Supply Line Inspection Sprinkler Plumbing Inspection Small Diameter Drains	Pools (1.5" pressure 90s) Toilet Traps Sink Traps Small Diameter Drains	Sewer Laterals Chimneys Floor Drains General Drain Inspection

The nanoReel Inspection Camera is compatible with the following CCUs



CS6x Monitor
Catalogue No. 56808



CS6x Pak Monitor
Catalogue No. 56818



CS65x Monitor
Catalogue No. 54368



CS12x Monitor
Catalogue No. 57283



**micro CA-350 Monitor
Inspection Camera**
Catalogue No. 57358