

CS65 DIGITAL REPORTING MONITOR

Complete Reporting Solution

One-touch image and video capture directly to one or two USB drives and the built-in 1 TB hard drive. The CS65 mounts to the SeeSnake Max rM200 for easy transport and storage.

Easily add on-screen titles and annotate captured media with the built-in keyboard and automatically generate high quality multimedia reports.



BENEFITS

- **One-touch recording** for fast, efficient documentation of inspections
- **1 TB internal hard drive** provides ample storage for multiple jobs
- **PhotoTalk™** pairs audio commentary with an image, in an email-ready file
- **Daylight viewable display** for a crisp, clear, in-pipe image
- **Water-resistant keyboard** makes it easy to add onscreen titles and annotate reports
- **HQ Software** to edit, archive, and deliver reports via print, DVD, or online

SPECIFICATIONS

- Weight (without battery) 9.8lb (4.4kg)
- Length 15.9" (403mm)
- Width 12.3" (312mm)
- Height 9.9" (251mm)
- Power Source 18V Advanced Lithium Battery or AC Adapter
- Power Rating 16 to 25 VDC, 30W
- Operating Temperature 14°F to 122°F (-10°C to 50°C)
- Storage Temperature -4°F to 140°F (-20°C to 60°C)
- Relative Humidity 5% to 95%
- Altitude 13,120' (4,000m)
- Display 6.5" (165mm) Colour LCD
- Resolution 640 x 480 VGA
- Video Format MPEG4 (H.264) 30 FPS
- Autolog Format MPEG4 (H.264) Low, Variable Frame Rate
Decreased File Size
- Image Format JPEG
- Audio Integrated Microphone and Speakers
- Transfer USB Drive

ORDERING INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.) (kg)	
48128	CS65	CS65 Digital Reporting Monitor (Battery and AC Adapter NOT included)	9.5	4.3
43328	—	18V Advanced lithium 4Ah battery	2.0	0.9
43323	—	18V Advanced lithium 2Ah battery	1.0	0.5
33193	—	Battery charger	3.1	1.4

For a **FREE DEMONSTRATION** contact your **RIDGID representative**
Subject to availability & location



RIDGID.COM/seesnake



RIDGID.COM.AU

