

RIDGID®

SeeSnake® NANOREEL® Inspection Camera



The RIDGID® SeeSnake® NANOREEL® opens up new possibilities in drain inspection with the smallest-diameter camera and most flexible push cable of all SeeSnake® systems. Inspect a wide array of specialty applications that previously only bore scopes could reach.

- Small 15.5 mm camera head with ultra flexible push cable navigates tight spaces in 1" to 2.5" lines
- A built-in kickstand offers in-field versatility with multiple configurations
- Lightweight and compact carrying case design is easy to carry to jobsites and store in-between
- Integrated 512 Hz sonde allows for easy line tracing and locating



SPECIFICATIONS

- Camera
 - Diameter..... 15.5 mm
 - Type..... Fixed
- Line Capacity 1" to 2 1/2"
(25 mm to 64 mm)
- Push Cable
 - Length 82' (25 m)
 - Diameter..... 0.28" (7.2 mm)
 - Minimum Bend Radius..... 1.5" (38 mm)
- Cable Flexibility..... Ultra Flex
- Sonde..... 512 Hz, Integrated
- Weight..... 12.1 lb. (5.5 kg)
- Length..... 13.3" (337 mm)
- Width..... 8.8" (224 mm)
- Height..... 16.2" (411 mm)
- Drum Diameter 12" (305 mm)

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(lb.)	(kg)
70038	SeeSnake® NANOreel	12.1	5.5

ACCESSORIES

CATALOG NO.	DESCRIPTION
42778	30 mm and 25 mm Pipe Guide Set, 15 mm Camera, Pkg of 2
70723	Kit, Slipping Connector w/3m Cable
70718	Kit, CA-350 Adapter, Slipping Connector w/3m Interconnect Cable
67808	Kit, CA-350 Adapter w/Docking Handle
55898	micro CA-350 Inspection Camera
69758	Kickstand Accessory
71498	Spare, Slipping Connector
67307	Interconnect Cable, 3m



Scan for more information on HQx Live

RIDGID.COM/seesnake