RIDGID

Standard Camera Reel with TruSense™

Equipped with the largest diameter SeeSnake® camera head, the Standard is your go-to machine for inspecting long runs in main sewer laterals. Everything about the Standard suggests durability, from the all-metal frame and hardened stainless steel camera head to the stiff cable. Newly available TruSense technology provides a high dynamic range (HDR) image sensor and a TiltSense™ inclinometer for SeeSnake CSx series Wi-Fi enabled monitors.

- First data enabled camera heads designed for drain inspection
- HDR image sensor offers bright, clear in-pipe imaging in difficult lighting conditions
- TiltSense data sensor displays the camera's pitch on CSx series Wi-Fi enabled monitors
- Self-leveling option ensures camera image is always upright
- Download the free HQx Live app to view and record video from a CSx series monitor on your phone or tablet

SPECIFICATIONS

- Camera Head ..... 30 mm TruSense™ fixed or self-leveling
- Light Source ..... High-Intensity LED
- Push Cable Length..... 200' (61 m)
- Push Cable Diameter.....0.36" (9.1 mm)
- Push Cable Minimum Bend Radius.....3' (76 mm)
- Line Capacity .....1.5' – 8' (38 mm – 203 mm)
- 512 Hz Sonde .....High-power FleXmitter
- Dimensions (LxWxH).....20.4" x 11.3" x 22" (519 x 288 x 560 mm)
- Operating Temperature ..... 14°F to 122°F (-10°C to 50°C)
- Storage Temperature..... 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor).....IPx5

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT (lb.)	(kg)
63628	200' Mini 30 mm SL TruSense	26	11,8
63633	200' Mini 30 mm TruSense	26	11,8

ACCESSORIES

CATALOG NO.	DESCRIPTION
67312	101 mm Star Guide, 30mm Camera, Pkg of 20
95507	Pipe Guide, 30 mm Camera, Pkg of 6
97462	101 mm Star Guide (pkg. of 20)
93392	Guide Hoop, 30 mm Camera, Pkg of 4
17558	Spanner Wrench, 30 mm

REPLACEMENT PARTS

CATALOG NO.	DESCRIPTION
63843	30 mm Self-Leveling Camera Head - TruSense
63848	30 mm Fixed Camera Head - TruSense
48533	30 mm Self-Leveling Camera Head - NTSC
14083	30 mm Fixed Camera Head - NTSC
67327	200' SeeSnake Mini Push Cable Assembly
67307	Interconnect Cable, 10’ Mini SeeSnake

HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging.

TiltSense™

Data sensor displays cameras in-pipe pitch.

Download on the App Store

GET IT ON Google play

HQx

RIDGID FULL LIFETIME WARRANTY Against Material Defects & Workmanship

All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-19-B (219) Effective Date: February 1, 2019
©2019 RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries.
All other trademarks belong to their respective holders.