

**MATERIAL SAFETY DATA SHEET**

---

**Section 1 – Product & Company Identification**

---

Product Name.....: RIDGID Thread Sealant  
(Gray Thread Sealant)  
Product Catalog No. ....: 84282, 84287, 84292  
  
Company Name.....: Ridge Tool Company  
Address .....: 400 Clark Street  
: Elyria, Ohio 44035-6001  
Telephone .....: 1-800-519-3456 (USA) (8:00 am – 5:00 pm EST, M-F)  
Emergency Telephone .....: call 9-1-1 or local emergency number  
  
Issue Date .....: September 15, 2011

---

**Section 2 – Hazards Identification**

---

**EMERGENCY OVERVIEW:**

This product is a gray paste with a mild petroleum odor. Direct eye contact may cause short term irritation. Skin exposure may cause mild irritation. Inhalation and ingestion are not anticipated routes of exposure during normal conditions of use.

**REGULATORY STATUS**

- This product is not listed as a known or suspected carcinogen by IARC, OSHA or the NTP.
- This product is not considered to be hazardous under OSHA's Hazard Communication Standard

**POTENTIAL HEALTH EFFECTS AND SYMPTOMS FROM SHORT TERM / ACUTE EXPOSURE:**

- Eye:  
This product is not expected to cause eye irritation under normal conditions of use. Direct contact may cause irritation.
- Skin:  
Short term skin contact may cause mild irritation. Prolonged or repeated direct exposure to the skin may cause dermatitis.
- Inhalation:  
Inhalation is not a likely route of entry.

Product Name.....: RIDGID Thread Sealant

---

- Ingestion:  
Ingestion may cause a laxative effect including cramps and diarrhea.
- Potential Chronic Health Effects:  
Chronic skin exposure may cause dermatitis.
- Medical Conditions Aggravated By Exposure:  
None known.

#### POTENTIAL ENVIRONMENTAL EFFECTS

None known.

HMIS Rating: Health – 0 Flammability – 0 Reactivity – 0 PPE: A

---

### Section 3 – Composition / Information On Ingredients

---

Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade secret components.

<u>Component:</u>	<u>CAS #</u>	<u>% By Weight</u>
Calcium Carbonate	1317-65-3	60 – 75
Hydrocarbon Oils	64742-52-5	20 – 30
Fish Oil	68082-77-9	1 - 5
Clay	68953-58-2	1 – 5

Product Name.....: RIDGID Thread Sealant

---

---

#### Section 4 – First Aid Measures

---

##### EYE CONTACT:

Upon direct eye contact, hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Call a physician if irritation persists.

##### SKIN CONTACT:

Remove product from the skin by washing with a mild soap and water. Contaminated clothing should be removed to prevent prolonged exposure. If symptoms of exposure persist, contact a physician.

##### INHALATION:

Inhalation is not a likely route of entry.

##### INGESTION:

Do not induce vomiting. Rinse mouth with water. Seek medical attention.

---

#### Section 5 – Fire Fighting Measures

---

##### FIRE AND EXPLOSIVE PROPERTIES:

Flashpoint.....: Not available  
Flammability Limits .....: LEL - Not determined  
UEL - Not determined

##### EXTINGUISH MEDIA:

In accordance with NFPA guidance, dry chemical, foam, or CO2 fire extinguishers are all acceptable. Water may be ineffective as an extinguishing media.

##### HAZARDOUS COMBUSTION PRODUCTS:

Combustion by-products may include carbon monoxide and carbon dioxide.

##### FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Emergency responders in the danger area should wear appropriate clothing/equipment for the surrounding fire.

##### NFPA RATING:

Health	Flammability	Reactivity
0	0	0

Product Name.....: RIDGID Thread Sealant

---

---

### **Section 6 – Accidental Release Measures**

---

#### **PERSONAL PRECAUTIONS:**

Use personal protection recommended in Section 8.

#### **ENVIRONMENTAL:**

Prevent discharge to waterways.

#### **CLEAN-UP MEASURES:**

Sweep up dried material and dispose of with ordinary trash.

---

### **Section 7 – Handling And Storage**

---

#### **HANDLING:**

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Follow all other standard industrial hygiene practices. Wash thoroughly after handling.

#### **STORAGE:**

Protect product quality by storing in a cool, dry area. Close all containers when not in use.

Product Name.....: RIDGID Thread Sealant

---

---

**Section 8 – Exposure Controls / Personal Protection**

---

**EXPOSURE GUIDELINES:**

<b>Component</b>		
Calcium Carbonate	ACGIH TLV: OSHA PEL:	10 mg / m3 15 mg / m3 (total dust)
Hydrocarbon Oil	ACGIH TLV: OSHA PEL:	5 mg / m3 5 mg / m3
Clays	ACGIH TLV: OSHA PEL:	10 mg / m3 10 mg / m3

**ENGINEERING CONTROLS:**

Good general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should, at a minimum, prevent airborne concentrations from exceeding any exposure limits shown above.

**PERSONAL PROTECTIVE EQUIPMENT:**

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. Employees should be properly trained to use appropriate PPE when working with this product.

- **Eye Protection:**  
Wear eye protection appropriate to prevent eye exposure. Safety glasses with side shields are recommended.
- **Skin Protection:**  
Gloves are not normally needed during normal conditions of use. If health effects are experienced, wear appropriate gloves.
- **Respiratory Protection:**  
No special requirements under ordinary conditions of use with adequate ventilation. A dust respirator should be worn during cleanup of dried material.

Product Name.....: RIDGID Thread Sealant

---

---

### Section 9 – Physical And Chemical Properties

---

Physical Appearance:.....: Gray Paste  
Odor. ....: Petroleum  
Physical State.....: Paste  
Water Solubility.....: Negligible  
Specific Gravity.....: 2.0 @ 70°F  
VOC .....: 3 g/L

---

### Section 10 – Stability And Reactivity

---

#### STABILITY:

This product is stable.

#### CONDITIONS TO AVOID:

Avoid sources of ignition.

#### INCOMPATIBLE MATERIALS:

This product is incompatible with oxidizing agents.

#### DECOMPOSITION PRODUCTS MAY INCLUDE:

Carbon monoxide and carbon dioxide.

#### HAZARDOUS POLYMERIZATION:

This product is not expected to polymerize.

Product Name.....: RIDGID Thread Sealant

---

---

### **Section 11 – Toxicological Information**

---

**ACUTE:**

Oral LD<sub>50</sub>: Not determined

Inhalation LC<sub>50</sub>: Not determined

**CHRONIC:**

Prolonged or repeated overexposure can cause dermatitis.

**SENSITIZATION:**

None of the components are known to cause sensitization.

**REPRODUCTIVE EFFECTS:**

None of the components are known to be toxic to reproduction.

**TERATOGENIC EFFECTS:**

No further teratogenic data known.

**MUTAGENICITY:**

None of the components are known to be a mutagen.

**CARCINOGENICITY:**

This product is not listed as a known or suspected carcinogen by IARC, OSHA or the NTP.

---

### **Section 12 – Ecological Information**

---

**ECOTOXICOLOGICAL INFORMATION:**

This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.

**ENVIRONMENTAL FATE:**

The degree of biodegradability and persistence of this product has not been determined.

**VOC CONTENT:**

3 g/L

Product Name .....: RIDGID Thread Sealant

---

---

### **Section 13 – Disposal Consideration**

---

#### **WASTE DISPOSAL:**

Ensure that collection, transport, treatment and disposal of waste product and containers complies with all applicable laws and regulations. Note that use, mixture, processing or contamination of the product may cause the material to be classified as a hazardous waste. It is the responsibility of the product user or owner to determine at the time of disposal whether the product is regulated as a hazardous waste.

---

### **Section 14 – Transportation Information**

---

#### **U.S. DOT HAZARDOUS MATERIAL INFORMATION:**

Not DOT regulated.

#### **CANADA TRANSPORT OF DANGEROUS GOODS:**

This material is not TDG regulated.

---

### **Section 15 – Regulatory Information**

---

#### **FEDERAL REGULATIONS:**

##### **SARA 313:**

This product contains NONE of the substances subject to the reporting requirements of Section 313 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

##### **SARA 302:**

This product contains NONE of the substances subject to the reporting requirements of Section 302 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 355.

##### **CERCLA REPORTABLE QUANTITY:**

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

None to report



Product Name.....: RIDGID Thread Sealant

---

**TOXIC SUBSTANCE CONTROL ACT:**

The components of this product are listed on the TSCA Inventory.

**STATE REGULATIONS**

California Proposition 65 : This product does not contain any chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**CANADA**

WHMIS Classification: Not controlled under WHMIS

---

**Section 16 – Other Information**

---

Prepared by: ..... Ridge Tool Company

Issue Date: ..... September 15, 2011

Last Revision Date: ..... September 30, 2009

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.