

K9-306 FlexShaft<sup>®</sup> Machine Clears 3" to 6" (75 to 150 mm) Pipe Up to 125' (38 m)



Purpose-built for the professional, the NEW RIDGID<sup>®</sup> FlexShaft K9-306 powered with I-Clutch<sup>™</sup> technology, quickly clears grease buildup, roots and heavy scale using 125' of 3/8" cable for 3" - 6" pipes with one step of the foot switch. It features a professional 1.5 HP internal universal motor for maximum power and longevity, a fully enclosed drum to minimize setup and cleanup time, and a telescoping handle with multiple wheels and grab points to make loading, unloading, transporting, and storage easy.

- Wall-To-Wall Clean: Chain knockers expand for full pipe cleaning
- Simultaneous Camera Use: FlexShaft machines let you keep your camera in-pipe while you work
- Continuous Power: Internal 1.5HP motor equipped with an I-Clutch<sup>™</sup> for additional cable protection
- Increase Productivity: Faster setup and cleanup, quick cleaning, and easy to transport for additional time savings
- Versatile Frame: Utilize 2 or all 4 wheels for ease of maneuverability and transport. Telescoping handle allows for a compact footprint in tight job site locations, while creating a low profile for storage

RIDGID<sup>®</sup> FlexShaft machines utilize specialized chain knockers and brushes attached to a flexible cable that are spun at high speeds. Since the cable spins inside a durable nylon sheath that is housed within a fully contained drum, there is less jobsite mess.

## **SPECIFICATIONS**

- Cable Assy. Diameter (with Sheath).....5/8" (16 mm)

- Operating temperature......20°F 140°F (-6°C 60°C)

## **ORDER INFORMATION**

CATAL	)G	MODEL	DESCRIPTION	WEIGHT	
NO.		NO.	DESCRIPTION	(lb.)	(kg)
66593	3	K9-306 NA	FlexShaft, K9-306 NA 3"-6" (75 mm - 150 mm) Pipes Includes: ¾" by 125' (10 mm x 38 m) cable and kit*	159	72.1

\* K9-306 includes: 4" Chain Knocker, 6" Chain Knocker, FlexShaft Lubricant, 4 mm Hex Key, 3 mm Hex Key, RIDGID Tool Bag, 12" Sheath Stock, 4" Sheath Spacer, 6" Sheath Spacer, Manual Pack.

## ACCESSORIES

CATALOG NO.	DESCRIPTION
66618	FlexShaft Knocker, ¾" (10 mm) cable, 3" (75 mm) pipe, 3 chain
66623	FlexShaft Knocker, ¾" (10 mm) cable, 4" (100 mm) pipe, 3 chain
66628	FlexShaft Knocker, ¾" (10 mm) cable, 5" - 6" (125 - 150 mm) pipe, 3 chain
66633	FlexShaft Knocker, ¾" (10 mm) cable, 3" (75 mm) pipe, 3 chain,carbide tip
66638	FlexShaft Knocker, ¾ (10 mm) cable, 4" (100 mm) pipe, 3 chain, carbide tip
66643	FlexShaft Knocker, ¾" (10 mm) cable, 5" - 6" (125 - 150 mm) pipe, 3 chain, carbide tip
66648	FlexShaft Knocker, ¾" (10 mm) cable, 3" (75 mm) pipe, 3 chain, penetrating head
66653	FlexShaft Knocker, ¾" (10 mm) cable, 4" (100 mm) pipe, 3 chain, penetrating head
66658	FlexShaft Knocker, ¾" (10 mm), 5" - 6" (125 - 150 mm) pipe, 3 chain, penetrating head
64338	RIDGID FlexShaft Lubricant, 8 oz
66663	FlexShaft %" (10 mm) Assembly, 125' (38 m) cable, sheath, couplings
66668	FlexShaft <sup>3</sup> / <sub>8</sub> " (10 mm) Sheath Stock, 12" (30 cm)
71858	FlexShaft Penetrating Tip, ¾" (10 mm) cable
68958	FlexShaft Nylon Brush, ¾" (10 mm) cable, 3" (75 mm) pip
68963	FlexShaft Nylon Brush, ¾" (10 mm) cable, 4" (100 mm) pipe
68968	FlexShaft Nylon Brush, 3/8" (10 mm) cable, 6" (150 mm) pipe
68988	FlexShaft Nylon/Steel Brush, 3/8" (10 mm) cable, 3" (75 mm) pipe
68993	FlexShaft Nylon/Steel Brush, 3/8" (10 mm) cable, 4" (100 mm) pipe
68998	FlexShaft Nylon/Steel Brush, 3/8" (10 mm) cable, 6" (150 mm) pipe

Standard Chain Knockers • Soft walled pipes • For soft blockages and grease

RIDGID



Carbide Tipped Chain Knockers • Hard walled pipes • For scale, roots, grease and soft blockages



Penetrating Head Chain Knockers • Hard walled pipes • For wipes, scale, roots, grease and soft blockages



## RIDGID.COM/FLEXSHAFT

