

SeeSnake® NANOreel® Inspection Reel

RIDGID®

NEW!



The RIDGID® SeeSnake® NANOreel® opens up different possibilities in specialized drain inspection by offering the smallest-diameter camera technology and most flexible push cable of all SeeSnake® systems. NANOreel allows you to inspect a wider array of specialty applications (small pipes, tubes, voids, and conduits) which conventional inspection systems often cannot inspect.

The included kickstand lets you set up the NANOreel in the optimal position for stability while pushing or retrieving the cable. The NANOreel is compatible with any SeeSnake device or combine it with the handheld RIDGID micro CA-350(x) Inspection Camera*.

- ▶ **Small 15.5 mm camera head with ultra flexible push cable navigates tight spaces in 25 to 50 mm (1" - 2") lines.**
- ▶ **A built-in kickstand offers in-field versatility and improved stability with multiple configurations.**
- ▶ **Lightweight and compact carrying case design is easy to carry to jobsites and store in-between.**
- ▶ **Integrated 512 Hz sonde allows for easy line tracing and locating.**

* Micro CA-350(x) inspection camera sold separately or in System SKU's.

SeeSnake® NANOreel® Inspection Reel

RIDGID®

SPECIFICATIONS:

Model		SeeSnake® NANOreel®
Camera	Diameter	15.5 mm
	Type	Fixed
Line Capacity		25 mm to 50 mm (1" to 2")
Push Cable	Length	25 m (82')
	Diameter	7,2 mm (0.28")
	Minimum Bend Radius	40 mm (1.5")
Cable Flexibility		Ultra Flex
Sonde		512 Hz, Integrated
Weight		5,5 kg (12.1 lb.)
Length		337 mm (13.3")
Width		224 mm (8.8")
Height		411 mm (16.2")
Drum Diameter		305 mm (12"), Interchangeable

*The NANOreel will traverse a 25 mm (1") straight pipe, but its ability to go past 90-degree turns will depend on the material and construction of individual pipes and joints. Some fittings in small diameter joints will allow passage of the camera in only one direction.



ORDERING INFORMATION:

Catalog No.	Description	Weight	
		lb.	kg
70038	SeeSnake® NANOreel®, Reel only	12	5,4
77583	System, NANOreel with CA-350 Inspection Camera	22,4	10,1
77598	System, NANOreel with CA-350x Inspection Camera with Wi-Fi	22,4	10,1

ACCESSORIES:

Cat. No.	Description
42778	30 mm and 25 mm Pipe Guide Set, 15 mm Camera, Pkg of 2
70723	Kit, Slipping Connector w/ 3 m Cable
70718	Kit, CA-350 Adapter, Slipping Reel Connector w/ 3 m Interconnect Cable
67808	Kit, CA-350 Adapter w/ Docking Handle
55903	micro CA-350 Inspection Camera
69758	Kickstand Accessory
71498	Spare, Slipping Connector
67307	Interconnect Cable, 3 m



For more details visit RIDGID.com/warranty

DISTRIBUTOR



Scan for
more information on HQx Live
RIDGID.COM/seesnake



RIDGID® reserves the right to change design and specification of our products without notification or alteration of literature. For the complete selection of the Ridge Tool product line, please refer to the RIDGID® Tool Catalog or RIDGID.com.

© 2023. RIDGID and the Emerson logo are registered trademarks of Emerson Electric Co. or its subsidiaries in the U.S. and other countries. All other trademarks belong to their respective holders.

RIDGID®

Ridge Tool Europe N.V.
Ondernemerslaan 5428
B-3800 Sint-Truiden
Belgium

Tel.: +32 (0)11 598 620
RIDGID.benelux@emerson.com
RIDGID.com



EMERSON™