

SAFETY DATA SHEET INFORMATION

RIDGID Product Name: OIL, 1 QT 10W-30 RIDGID Product Catalog No.: 27808796110

Vendor Name: VALVOLINE

Vendor Product Name: NAPA® PREMIUM CONVENTIONAL SAE

10W-30 MOTOR OIL

Use in RIDGID Products: Used for KJ2200 and KJ-3100 Water Jetting

Machines Pumps

Restrictions on Use: NA

SDS Information See following sheets for manufacturer SDS

Ridge Tool Contact Information:

North America	Australia	Europe
Ridge Tool Company	Ridge Tool Australia	Ridge Tool Europe NV (RIDGID)
400 Clark Street	127 Metrolink Circuit	Ondernemerslaan 5428
Elyria, Ohio 44035-6001	Campbellfield, VIC 3061	3800 Sint-Truiden, Belgium
1-800-519-3456	1-800-743-443	+32 (0) 11 598 640
www.RIDGID.com	www.RIDGID.com.au	www.RIDGID.eu

Operating Standard: 6-209
Revision: B
EC Number 45297

Issue Date: October 1, 2020 Last Revision Date August 13, 2018

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.

Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

NAPA® PREMIUM CONVENTIONAL SAE 10W-30

MOTOR OIL

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet
Valvoline LLC
3499 Blazer Parkway
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL

Emergency telephone number
1-800-VALVOLINE

Regulatory Information Number
1-800-TEAMVAL

Product Information
1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60- alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.225
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	2.8117

SECTION 4. FIRST AID MEASURES

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

General advice

: No hazards which require special first aid measures.

If inhaled

: If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

: First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact

Remove contact lenses.

Protect unharmed eye.

If swallowed

: Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information

: Standard procedure for chemical fires.

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information

: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid

: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

(Form of parameters / exposure) Permissible concentration	Components	CAS-No.	A COMPANIAN PROPERTY OF THE PR	Permissible	Basis
---	------------	---------	--	-------------	-------

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	= "

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
(2)		TWA	5 mg/m3 Mist	NIOSH REL
1		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

The second of th	
Components	CAS-No.
Benzenesulfonic acid, C10-60- alkyl derivs., sodium salts	90194-32-4

Engineering measures

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally

required.

Eye protection

Not required under normal conditions of use. Wear splashproof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection

Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures

: General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

: liquid

Odour

: No data available

Odour Threshold

: No data available

рΗ

: No data available

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

Melting point/freezing point

: No data available

Boiling point/boiling range

: No data available

Flash point

> 199 °C

Method: Cleveland open cup

Evaporation rate

: No data available

Flammability (solid, gas)

: No data available

Upper explosion limit

: No data available

Lower explosion limit

: No data available

Vapour pressure

: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure

Relative vapour density

: No data available

Relative density

: No data available

Density

: 0.8686 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility

: No data available

Solubility in other solvents

: No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition

Viscosity

Viscosity, dynamic

: No data available

No data available

Viscosity, kinematic

: 70 mm2/s (40 °C)

Oxidizing properties

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No decomposition if stored and applied as directed.

Chemical stability

: Stable under recommended storage conditions.

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
NADAO PREMIUM COMPTUENTO	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid

: excessive heat

Incompatible materials

: Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: No skin irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity

: Not classified based on available information.

Chronic aquatic toxicity

: Not classified based on available information.

Persistence and degradability

No data available

Bioaccumulative potential

No data available **Mobility in soil** No data available

Other adverse effects

No data available

Product:

information

Additional ecological

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging

: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

	Valve					Page: 8
	Valv		TM.			
SAFETY DA	ATA SHEET				00.0004660478.2500.000	Date: 09/28/2016
						nt Date: 10/3/2016
NAPA® PREMIL	JM CONVENTIONAL SAE 1	0W-30 MOTOR O	п		SDS N	umber: R0170829 Version: 1.2
NP75130						VG131011. 1.2
ID NUMBER	PROPER SHIPPING NAM	1E *HAZARD	SUBSI	DIARY	PACKING	MARINE
	Service sounds sound soundary services designed stands determined	CLASS	HAZAF		GROUP	POLLUTANT / LTD. QTY.
U.S. DOT - ROA					2 2	
	Not dangerous goods					
CFR_RAIL_C						
	Not dangerous goods					
U.S. DOT - INLAN	D WATERWAYS Not dangerous goods					
	Not dangerous goods					
TDG_ROAD_C						
	Not dangerous goods	7				
	F					
TDG_RAIL_C	Not dongovous as a de					
	Not dangerous goods					
TDG_INWT_C						
	Not dangerous goods					
NTERNATIONAL					-	
NIERNATIONAL	MARITIME DANGEROUS Not dangerous goods	GOODS				1
NTERNATIONAL	AIR TRANSPORT ASSOC	IATION - CARGO				
	Not dangerous goods					
NTERNATIONAL	AID TRANSPORT ASSOCI	ATION BAGGE				
NIERNATIONAL	AIR TRANSPORT ASSOCI	ATION - PASSEN	GER			
/IX_DG						
	Not dangerous goods					
ORM = ORM-D, C	BL = COMBUSTIBLE LIQU	JID				
Marine pollu						
police						

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
NADAO DEGMUMA CONTUENTIONAL CONTUENTIONAL	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards

: No SARA Hazards

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

WARNING! This product contains a chemical known to the

State of California to cause cancer. 91-20-3

NAPHTHALENE

The components of this product are reported in the following inventories:

TSCA

: On TSCA Inventory

DSL

: All components of this product are on the Canadian DSL

AICS

: On the inventory, or in compliance with the inventory

ENCS

: Contact your sales representative for additional information.

KECI

: On the inventory, or in compliance with the inventory

PICCS

: On the inventory, or in compliance with the inventory

IECSC

: Low volume exemption

IECSC

: q (quantity restricted)

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/28/2016

NFPA:	HMIS III:	
-------	-----------	--

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
NADAO DDEMI IN CONVENTIONAL OLD INVINIONAL	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements
H304
M

May be fatal if swallowed and enters airways.

H319

Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 09/28/2016
	Print Date: 10/3/2016
NADAO DEGAMENA CON TUTION OF	SDS Number: R0170829
NAPA® PREMIUM CONVENTIONAL SAE 10W-30 MOTOR OIL	Version: 1.2
NP75130	

IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System