





The NEW RIDGID® StrutSlayr is the latest accessory that makes the world's most popular press tool even more valuable. StrutSlayr attaches to RIDGID® 32kN press tools to deliver a fab shop quality, burr-free cut in 5 seconds or less.

No grinding or sawing sparks - just a clean, consistent SHEAR cut with a pull of a trigger.

- ► Fab Shop Quality: Burr-free cuts eliminate the need for extra filing
- ▶ Increased Efficiency: Clean, consistent cuts in 5 seconds or less
- ► Shear Cut: no grinding or sawing sparks
- ▶ Portable: Easy to move around the job site and mounts to RIDGID TRISTANDs
- ▶ Built-in Measuring Guide: allows accuracy of cut on job site







SPECIFICATIONS

Cutting Capability	41 x 41 mm or 21 x 41 mm strut channels
	(max. 2.5 mm wall-thickness).
	Not for use with Stainless Steel strut
Weight of Head	5.8 kg (including dies, not including press tool)
Press Tool	RIDGID® Standard Series 32kN Press Tools
Compatibility	(Such as the RP340 and RP330). Not for use with RIDGID 320-E and CT-400 Press Tools.
Cut Squareness	+/- 2° (Strut must extend past strut support)
Shearing Dies	21 x 41 mm Die (Cat. No. 64033)
	41 x 41 mm Die (Cat. No. 64038)

ORDERING INFORMATION

Cat. No.	Description	Weight/Kg
64033	Die Shear - 21 x 41 mm	1.29
64038	Die Shear - 41 x 41 mm	1.29
64048	Case, Carrying-Strutslayr	2.93
64053	Kit, Head + Case + 21 x 41 mm Dies	8.96
64058	Kit, Head + Case + 41 x 41 mm Dies	8.96
64118	Strutslayr Head	4.74

Available Dies:







Register your tool on RIDGID Link™ App

LET'S KEEP IN TOUCH • RIDGID.EU/SIGNUP













© 2021. RIDGID and the Emerson logo are registered trademarks of Emerson Electric Co. or its subsidiaries in the U.S. and other countries.

RIDGID® reserves the right to change design and specification of our products without notification or alteration of literature. For the complete selection of the Ridge Tool product line, please refer to the RIDGID® Tool Catalog or **RIDGID.com**.

DISTRIBUTOR



