



Compact C40 Camera Reel

For a **FREE DEMONSTRATION***
contact your **RIDGID representative**

*Selected products only & subject to availability & location



Monitor pictured available separately.

RIDGID® SeeSnake® Compact C40 camera reel delivers big performance in a small package. Compatible with the new SeeSnake CS6x Versa digital reporting monitor for fast set-up and easy viewing, while built-in Wi-Fi and Bluetooth make live streaming and inspection to an iOS™ or Android™ device simple with the free HQx Live app.

- 25mm self-leveling camera head provides a crisp image that is always upright
- TruSense™ technology features two-way communication between the camera and a CSx series Wi-Fi enabled monitor
- High dynamic range image sensor provides bright, saturated images with improved detail, even in difficult lighting conditions
- TiltSense inclinometer lets you know camera's degree of tilt inside the pipe when used with a CSx series monitor
- Equipped with high power FleXmitter® 512Hz sonde which is compatible with all RIDGID locators
- Download the free HQx Live app to view and record inspection jobs on your phone or tablet
- Use with the SeeSnake CS6x Versa to create the optimal viewing angle and for fast, efficient job setup



RIDGID.COM.AU

CONNECT WITH US

- [ridgid australia](#)
- [RIDGID Tools](#)
- [ridgid_australia](#)

REQUEST A DEMONSTRATION

Scan the QR code to request a demonstration or use this web address




www.ridgid.com/au/en/request-demonstration



SPECIFICATIONS

- Light Source..... High-Intensity LED
- Push Cable Length..... 131' (40m)
- Push Cable Minimum Bend Radius..... 2.5" (64mm)
- 512 Hz Sonde..... High-power FleXmitter®
- Dimensions (LxWxH)..... 626mm x 360mm x 429mm
- Operating Temperature..... -10°C to 50°C
- Storage Temperature..... -10°C to 70°C
- Ingress Protection (without Monitor)..... IPx6

COMPACT C40 CAMERA REEL

| CAMERA REEL | CAMERA HEAD | PUSH CABLE | MINIMUM BEND RADIUS | LINE CAPACITY |
|---|---|------------|---------------------|--------------------------|
| Compact C40 Camera Reel  | 25mm (1") Self-Leveling w/TruSense Technology | 131' (40m) | 2.5" (64mm) | 1.5" - 6" (38mm - 152mm) |

ORDERING INFORMATION

| CATALOG NO. | DESCRIPTION | WEIGHT (lb.) (kg) | |
|-------------|-------------------------|-------------------|-----|
| 63668 | Compact C40 (Reel Only) | 17.2 | 7.8 |

ACCESSORIES

| CATALOG NO. | DESCRIPTION |
|-------------|---|
| 47793 | 36mm Pipe Guide, 25mm Camera, Pkg of 1 |
| 35338 | 45mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 97462 | 60mm Pipe Guide, 25mm Camera, Pkg of 6 |
| 46708 | 85mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 46713 | 125mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 63868 | Various Pipe Guides, 25mm Camera Head |
| 17553 | Spanner Wrench, 25mm |



HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging..



TiltSense™

Data Sensor displays camera's angle in pipe.



Scan for more information on HQx Live



[RIDGID.COM/au/en/reels-and-cameras](https://www.ridgid.com/au/en/reels-and-cameras)

Ridge Tool (Australia) Pty Ltd ABN 96 008 446 482 • 127 Metrolink Circuit Campbellfield Victoria 3061
Phone 1800 743 443 Fax 1800 801 976 Email ridgid.australia@emerson.com Web www.ridgid.com.au

All sales subject to Ridge Tool Company Terms and Conditions of Sales.

All pictures shown are for illustrative purpose only and may not be an exact representation of the product.

999-997-412.10
Effective Date: March 17, 2022