

# 760 FXP™ Power Drive



Thread pipe quickly and precisely with the battery powered RIDGID® 760 FXP™ Power Drive. The FXP™ Technology Platform offers portability and provides the power to achieve up to 30 2" threads per charge.\* Sensors within the tool detect kickback and automatically shut it off for added control. The Power Drive delivers industry-leading speed with added features like workspace lights and LED alerts when the thread is nearing completion. This tool provides everything you need to get the job done.

- FXP Battery Power: Delivers 30 2" threads per charge\*, providing long-lasting run time on professional-grade tools
- Speed: Cut high quality threads on 1/2" 2" pipe and conduit faster than the competition\*\*
- Control: Tool automatically shuts off when kickback is detected
- Convenience: LEDs illuminate the die head and notify the user when the thread is nearing completion
- Brushless motor: Provides optimal output, enhances efficiency, and reduces downtime with no scheduled maintenance
- Smart: RIDGID Link app provides information to better understand tool usage, performance, and maintenance needs

\*With a fully charged 4Ah battery on 2" Schedule 40 pipe. \*\*Faster on 1-1/2"-2" Schedule 40 Pipe.





#### **CONNECT WITH US**

f ridgid australia

RIDGID Tools

ridgid\_australia



Scan the QR code to request a demonstration or use this web address



## **SPECIFICATIONS**

<ul> <li>PI</li> </ul>	ipe Threadi	ing Capacity	Pipe	1/8" to 2'	' (3 to 50mm)	
------------------------	-------------	--------------	------	------------	---------------	--

•	<b>Bolt Threading Capacit</b>	yBolt 1/4" ·	to 1"	(6 to 25mm	) with 00-RB Die Head
---	-------------------------------	--------------	-------	------------	-----------------------

Die Type ...... High Speed Dies Recommended

• Support arm ......No. 692

Power Source ...... RIDGID RB-FXP40 or RB-FXP80 Battery Pack

Motor Type ...... Brushless DC Motor

• Watts ......1080 W

• Operating Speed (RPM) ......42 RPM, no load

Controls ...... Forward/Reverse Slide Switch and ON/OFF Momentary Contact Switch

• Operating Temperature .....-4°F to 140°F (-20°C to 60°C)

Bluetooth Range ...... 33 ft (10m)

• Weight (No Battery) ......24 lb (10.9 kg)

Model	760 FXP 12-R	760 FXP 11-R
Die head holding	12-R Die Head	11-R Die Head
	Retaining Mechanism*	Retaining mechanism (11/2"-2")*
		Ring Spring (1/8"-11/4")*
Ratcheting Ring (cat # 39187)	Not required	Used with die 1/8" to 11/4"*

<sup>\*</sup>optional

### **ORDER INFORMATION**

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (kg.)
71993	760 FXP	POWER DRIVE, 760 FXP 12-R, c/w 692 support arm & Case ONLY ^	23.7
71998	760 FXP	POWER DRIVE, 760 FXP 11-R, c/w 692 support arm & Case ONLY ^	23.7
72133	760 FXP	POWER DRIVE, 760 FXP 12-R, c/w 692 support arm, case, 2 x 4.0Ah Batteries and 1 x Charger	30.2
72138	760 FXP	POWER DRIVE, 760 FXP 11-R, c/w 692 support arm, case, 2 x 4.0Ah Batteries and 1 x Charger	30.2
72143	760 FXP	POWER DRIVE, 760 FXP 12-R, c/w 692 support arm, case, 2 x 4.0Ah Batteries, 1 x Charger and die head 12-R HS kit 1/2-2" BSPT	47.4
72148	760 FXP	POWER DRIVE, 760 FXP 11-R, c/w 692 support arm, case, 2 x 4.0Ah Batteries, 1 x Charger and die head 11-R HS kit 1/2-2" BSPT	47.4

<sup>^</sup> battery, charger and die head not included

## **ACCESSORIES**

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (kg.)
70788	RB-FXP40	FXP Battery- 4.0 Ah	2.1
70793	RB-FXP80	FXP Battery- 8.0 Ah	3.4
71903	RBC-FXP	FXP Battery Charger	1.9
71983	_	12-R High Speed NPT Die Set (1/2"-2")	17.2
71988	_	11-R High Speed NPT Die Set (1/2"-2")#	14.2
74483	_	12-R High Speed BSPT Die Set (1/2"-2")	17.2
74498	_	11-R High Speed BSPT Die Set (1/2"-2")#	14.1
45928	692	692 Support Arm	3.6

Note: 12-R Tool Compatible with the 258 & 258XL Large Diameter Pipe Cutters.\*Adaptor Cat #42610 is required to use a 11R diehead on a 12R Tool.



760 FXP with case, 2 x 4Ah batteries & charger



