



SeeSnake® Standard DSL

No moving parts. The most rugged self-leveling camera.



The RIDGID® SeeSnake® Standard DSL is your go-to machine for inspecting long runs. Equipped with a digital self-leveling camera head to keep the image level during the inspection, it provides a smooth viewing experience with no moving parts. TruSense technology provides a high dynamic range (HDR) image sensor and a TiltSense™ inclinometer for SeeSnake CSx series Wi-Fi enabled monitors. All SeeSnake Camera Systems are field-serviceable on key components such as the camera head, interconnect cord, spring and Flexmitter® sonde. Diagnosing and replacing components is straight-forward and simple, saving you from unnecessary downtime.

- Digital Self Leveling: Our most advanced self-leveling camera has no moving parts, which maximizes uptime while always retaining a smooth & upright on screen image
- High Dynamic Range (HDR): Superior clarity and detail, allowing to quickly and easily identify problem areas
- TiltSense™ Inclinometer: Measures the camera's degree of tilt and displays on the monitor
- Digital Zoom/Pan: Zoom in and pan within the image to focus on points of interest



SPECIFICATIONS

- Camera Head 35 mm TruSense™ Digital Self-Leveling
- Light Source High-Intensity LED
- Push Cable Length 200' (61 m)//325' (99 m)
- Push Cable Diameter 0.44" (11.2 mm)
- Push Cable Minimum Bend Radius 4.5" (114 mm)
- Line Capacity 2" to 12" (51 mm to 305 mm)
- 512 Hz Sonde High-power Flexmitter®
- Dimensions (LxWxH) 32.7" x 17.7" x 29.8"
830 mm x 450 mm x 756 mm
- Operating Temperature 14°F to 122°F (-10°C to 50°C)
- Storage Temperature 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor) IPx5

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT (lb.) (kg)	
78733	200' TruSense Standard DSL	43	19.6

ACCESSORIES

CATALOG NO.	DESCRIPTION
64497	75 mm Star Guide, 35 mm Camera, Pkg of 20
97852	85 mm Pipe Guide, 35 mm Camera, Pkg of 10
64502	150 mm Star Guide, 35 mm Camera, Pkg of 10
93387	Guide Hoop, 35 mm Camera, Pkg of 4
97832	75 mm Roller Dolly, up to 6" Pipe
17563	Spanner Wrench, 35 mm
68568	Kit, Via Adapter -STD and Mini Reels

REPLACEMENT PARTS

CATALOG NO.	DESCRIPTION
14823	Spring -Standard
67307	Interconnect Cord, 3 m (10')
15323	Flexmitter® (single safety cable - Standard/Mini/Mini Pro/Compact2/C40/M40/rM200)



Scan for more
information on HQx Live



[RIDGID.COM/seesnake](https://www.ridgid.com/seesnake)