

RIDGID®

SeeSnake® MINI PRO

TruSense®
Enabled

For a FREE DEMONSTRATION*
contact your **RIDGID representative**

*Selected products only & subject to availability & location



12:05:54 PM / 01-30-2023



The RIDGID® SeeSnake® Mini Pro is our newest TruSense-enabled diagnostic inspection reel. With our smallest and most rugged 25mm self-leveling camera and mid-flex push cable, the Mini Pro is designed to navigate hard 90° bends and inspect up to 61m [200ft]. When used with a TruSense-capable monitor, the Mini Pro's innovative self-leveling technology produces the most stable in-pipe view, without mechanical rotation.

- Perform a variety of inspections with mid-flex push cable and our most compact self-leveling camera, ideal for inspecting 38mm to 203mm [1.5in to 8in] lines up to 61m [200ft]
- Ultra-smooth digital self-leveling keeps image upright without moving components
- TruSense technology in the Mini Pro enables the following features when used with a TruSense-capable monitor:
 - Digital self-leveling
 - High dynamic range (HDR) imaging for superior imaging in the pipe
 - TiltSense™ inclinometer, which gives you the pitch of the camera in the pipe
 - Digital pan/zoom to focus on points of interest
- Powerful 512Hz FleXmitter® sonde to locate points of interest in the pipe using a RIDGID SeekTech or NaviTrack receiver

RIDGID
INNOVATIVE
DURABLE
RELIABLE



RIDGID.COM.AU



CONNECT WITH US

-  ridgid australia
-  RIDGID Tools
-  ridgid_australia

SPECIFICATIONS

- Weight..... 11.8kg [26lb]
- Length..... 519mm [20.4in]
- Width..... 288mm [11.3in]
- Height..... 560mm [22in]
- Drum Diameter..... 462mm [18.2in]
- Camera Diameter..... 25mm [1in]
- Camera Length..... 18mm [0.7in]
- Type..... Digital Self-Leveling
- Resolution..... 640 x 480
- Line Capacity..... 38mm to 203mm [1.5 to 8in]
- Push Cable Length..... 61m [200ft]
- Push Cable Diameter..... 9.1mm [0.36in]
- Push Cable Minimum Bend Radius.... 76mm [3in]
- Sonde..... 512 Hz, FlexMitter

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT (kg) (lb)
76883	SeeSnake Mini Pro with TruSense 200'	11.8 26

ACCESSORIES

CATALOG NO.	DESCRIPTION
47793	36mm Pipe Guide, 25mm Camera, Pkg of 1
35338	45mm Pipe Guide, 25mm Camera, Pkg of 2
46708	85mm Pipe Guide, 25mm Camera, Pkg of 2
46713	125mm Pipe Guide, 25mm Camera, Pkg of 2
63868	Various Pipe Guides, 25mm Camera Head
17553	Spanner Wrench, 25mm

REPLACEMENT PARTS

CATALOG NO.	DESCRIPTION
67327	Kit, 200' Production Cable & Main Spring – Mini
64028	Kit, TruSense Counter for Standard and Mini
67307	Assy, Interconnect Cable, Overmolded, 3m (10')



HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging.



TiltSense™

Data sensor displays cameras in-pipe pitch.



RIDGID.COM/seesnake



Ridge Tool (Australia) Pty Ltd ABN 96 008 446 482 • 127 Metrolink Circuit Campbellfield Victoria 3061
Phone 1800 743 443 Fax 1800 801 976 Email ridgid.australia@emerson.com Web www.ridgid.com.au

All sales subject to Ridge Tool Company Terms and Conditions of Sales.

R-1038
Effective Date: August 30, 2023