



# SeeSnake® rM200 Camera Reel with TruSense®

For a **FREE DEMONSTRATION\***  
contact your **RIDGID representative**

\*Selected products only & subject to availability & location



CS65XR monitor pictured available separately.

The new RIDGID® SeeSnake® rM200 Camera Reel now features TruSense® technology for superior image clarity and camera functionality. Already known for its built-in versatility and portability, the rM200, now also has enhanced transportation and storage features. The interchangeable D2 Series Drums (D2A & D2B) provide various combinations of cable stiffness and spring flexibility to tackle any inspection job.

- **Enhanced camera functionality** – TruSense technology with High Dynamic Range (HDR) sensor and TiltSense™ inclinometer give crisp, always upright images and feedback on camera angle in-pipe
- **Interchangeability** – Easily interchangeable D2 drums for on-the-job flexibility and compatible with all SeeSnake monitors
- **Pushability** – Drums feature different push cable lengths, diameters, stiffness and springs for customized jobs
- **Portability** – Multi-functional pull handle and smooth wheels for easy transport and positioning
- **Increased storage** – New taller stow bins with increased internal capacity to store



RIDGID.COM.AU

#### CONNECT WITH US

ridgid australia

RIDGID Tools

ridgid\_australia

#### REQUEST A DEMONSTRATION

Scan the QR code to request a demonstration or use this web address



[www.ridgid.com/au/en/request-demonstration](http://www.ridgid.com/au/en/request-demonstration)



**rM200A Reel**  
Catalog No. 63658

## SPECIFICATIONS

### rM200A

- Length..... 21.0" (535mm)
- Width..... 13.6" (345mm)
- Height..... 24" (610mm)
- Drum Diameter..... 17" (432mm)
- Camera
  - Diameter..... 1" (25mm)
  - Type..... Self-leveling w/TruSense
  - Resolution..... 640 x 480
- Spring Assembly
  - Type..... Single
  - Length..... 12.4" (316mm)
- Line Capacity..... 1.5" – 8"  
(38mm – 203mm)
- Push Cable
  - Length..... 200' (61m)
  - Diameter..... 0.3" (7.5mm)
  - Minimum Bend Radius..... 2.8" (70mm)
- Sonde..... 512 Hz, Flexmitter®

## ORDERING INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.) (kg)	
63658	rM200A	Reel, SeeSnake rM200A w/D2A Drum, TruSense	37.0	16.7
70758	D2A	Drum, rM200 D2A, TruSense	16.3	7.4
70763	D2B	Drum, rM200 D2B, TruSense	19.2	8.7



**rM200 D2A Drum**  
Catalog No. 70758



**rM200 D2B Drum**  
Catalog No. 70763



Scan for more information on HQx Live



**RIDGID.COM/seesnake**

Ridge Tool (Australia) Pty Ltd ABN 96 008 446 482 • 127 Metrolink Circuit Campbellfield Victoria 3061  
Phone 1800 743 443 Fax 1800 801 976 Email [ridgid.australia@emerson.com](mailto:ridgid.australia@emerson.com) Web [www.ridgid.com.au](http://www.ridgid.com.au)

All sales subject to Ridge Tool Company Terms and Conditions of Sales.

All pictures shown are for illustrative purpose only and may not be an exact representation of the product.

999-997-969.10  
Effective Date: March 18, 2022