

RIDGID®

SeeSnake®

MINI PRO

TruSense®
Enabled



The RIDGID® SeeSnake® Mini Pro is our newest TruSense-enabled diagnostic inspection reel. With our smallest and most rugged 25 mm self-leveling camera and mid-flex push cable, the Mini Pro is designed to navigate hard 90° bends and inspect up to 61 m [200 ft]. When used with a TruSense-capable monitor, the Mini Pro's innovative self-leveling technology produces the most stable in-pipe view, without mechanical rotation.

- Perform a variety of inspections with mid-flex push cable and our most compact self-leveling camera, ideal for inspecting 38 mm to 203 mm [1.5 in to 8 in] lines up to 61 m [200 ft]
- Ultra-smooth digital self-leveling keeps image upright without moving components
- TruSense technology in the Mini Pro enables the following features when used with a TruSense-capable monitor:
 - Digital self-leveling
 - High dynamic range (HDR) imaging for superior imaging in the pipe
 - TiltSense™ inclinometer, which gives you the pitch of the camera in the pipe
 - Digital pan/zoom to focus on points of interest
- Powerful 512 Hz FleXmitter® sonde to locate points of interest in the pipe using a RIDGID SeekTech or NaviTrack receiver



SPECIFICATIONS

- Weight 11.8 kg [26 lb]
- Length..... 519 mm [20.4 in]
- Width 288 mm [11.3 in]
- Height 560 mm [22 in]
- Drum Diameter 462 mm [18.2 in]
- Camera Diameter 25 mm [1 in]
- Camera Length..... 18 mm [0.7 in]
- Type Digital Self-Leveling
- Resolution..... 640 × 480
- Line Capacity 38 mm to 203 mm [1.5 to 8 in]
- Push Cable Length..... 61 m [200 ft]
- Push Cable Diameter..... 9.1 mm [0.36 in]
- Push Cable Minimum Bend Radius.... 76 mm [3 in]
- Sonde 512 Hz, FleXmitter

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(kg)	(lb)
76883	SeeSnake Mini Pro with TruSense 200'	11.8	26

ACCESSORIES

CATALOG NO.	DESCRIPTION
47793	36 mm Pipe Guide, 25 mm Camera, Pkg of 1
35338	45 mm Pipe Guide, 25 mm Camera, Pkg of 2
46708	85 mm Pipe Guide, 25 mm Camera, Pkg of 2
46713	125 mm Pipe Guide, 25 mm Camera, Pkg of 2
63868	Various Pipe Guides, 25 mm Camera Head
17553	Spanner Wrench, 25 mm



REPLACEMENT PARTS

CATALOG NO.	DESCRIPTION
67327	Kit, 200' Production Cable & Main Spring – Mini
64028	Kit, TruSense Counter for Standard and Mini
67307	Assy, Interconnect Cable, Overmolded, 3m (10')



RIDGID.COM/seesnake