



**micro DM-100**

Digital Multimeter  
Drop- & Waterproof



**micro CM-100**

Digital Clamp Meter  
Versatile, 10 Functions



**micro HM-100**

Temp. Humidity Meter  
Accurate Measurements

## FULL RANGE OF TEST & MEASUREMENT DEVICES



**micro CL-100**  
Self-Leveling  
Cross-Line Laser



**micro LM-100**  
Laser Distance  
Meter



**micro IR-100**  
Non-Contact  
Infrared Thermometer



**micro CD-100**  
Combustible  
Gas Leak Detector



- IP 67 WATERPROOF & DROP-PROOF
- 11 FUNCTIONS IN ONE
- TRUE RMS / AUTORANGING

**NEW**



**37423**

**£ 85.-**

## micro DM-100 Digital Multimeter

The RIDGID® **micro DM-100 Digital Multimeter** sets the new standard for troubleshooting most of the electrical problems! Featuring a double molded water-resistant (1m) IP67 housing, the micro DM-100 is also drop-proof and perfectly suitable for use in the harshest jobsite conditions.

The micro DM-100 is a **True RMS** and **AutoRanging** unit, providing the most accurate and fast measurements in all applications. It features 11 different electrical functions ranging from AC/DC Voltage & Current (1000V) to Temperature measurements. The micro DM-100 is also rated for industrial use (CAT III-1000V & IV-600V) and features an Extra Large Backlit LCD display for easy and clear readings.

The micro DM-100 is supplied in a soft carrying case with double-molded test leads, Type K temperature probe and a 9V battery.



### Functions & Range

<b>Voltage AC/DC:</b>	400.0mV – 1000V
<b>Current AC/DC:</b>	400.0µA – 10A
<b>Resistance:</b>	400.0Ω – 40.00MΩ
<b>Capacitance:</b>	4.000nF – 200.0 µF
<b>Frequency:</b>	9.999Hz – 9.999MHz
<b>Duty Cycle:</b>	0,1% - 99,9%
<b>Diode Check:</b>	1.5V
<b>Continuity Test:</b>	150Ω
<b>Temperature:</b>	-20°C – 760°C

### Specifications

<b>Power Source:</b>	9V Battery (included)
<b>Display:</b>	4000 Count Backlit LCD
<b>Overload Protection:</b>	CAT III & IV 1000V/600V
<b>Fuses:</b>	2x, 0.5A & 10A- 1000V
<b>Insulation:</b>	Class II, Double Molded
<b>IP Rating:</b>	IP-67 Water-Resistant (1m)
<b>Polarity Indication:</b>	Yes, Automatic
<b>Auto Power-Off:</b>	Yes, After 15 Minutes
<b>AutoRanging:</b>	Yes
<b>Manual Ranging:</b>	Yes (single button)
<b>True RMS:</b>	Yes



- LARGE CAPACITY & MEASURING RANGE
- 10 FUNCTIONS IN ONE
- AUTORANGING / TRUE RMS

**NEW**



**37428**

**£ 85.-**

## micro CM-100 Digital Clamp Meter

The **micro CM-100** is a True RMS & AutoRanging Digital Clamp Meter with a large capacity and measuring range.

It can clamp around cables up to 30 mm O.D. and measure current up to 1000A AC/DC. Besides measuring AC/DC Current, the micro CM-100 can also be used as a Multimeter for 8 other functions and will provide clear and accurate readings on its large Backlit LCD.

The slim and double-molded design provides easy one-handed operation and can be conveniently used in confined cable compartments.

**Included in the micro CM-100 offering are:**  
soft carrying case, test leads, Type K temperature probe and 9V battery.



### Functions & Range

<b>Voltage AC/DC:</b>	400mV – 600V
<b>Current AC/DC:</b>	40A – 1000A
<b>Resistance:</b>	400Ω – 40MΩ
<b>Capacitance:</b>	4nF – 40mF
<b>Frequency:</b>	up to 4 kHz
<b>Diode Test:</b>	1.5V
<b>Continuity Test:</b>	35Ω
<b>Temperature:</b>	-40°C – 1000°C

### Specifications

<b>Power Source:</b>	9V Battery (included)
<b>Display:</b>	4000 Count Backlit LCD
<b>Clamp Size:</b>	Max. 30 mm O.D. Cable
<b>Overload Protection:</b>	CAT III 600V
<b>Polarity Indication:</b>	Yes, Automatic
<b>Auto Power-Off:</b>	Yes, After 20 Minutes
<b>AutoRanging:</b>	Yes
<b>True RMS:</b>	Yes
<b>AC/DC Current Range:</b>	40A/400A/1000A
<b>Data &amp; Peak Hold:</b>	Yes
<b>Bargraph Display:</b>	Yes



- EASY & ACCURATE MEASUREMENTS OF AIR TEMPERATURE & HUMIDITY
- DEW POINT AND WET-BULB CALCULATION

**NEW**



**37438**

**£ 85.-**

## micro HM-100 Temperature Humidity Meter

The **micro HM-100** Temperature Humidity Meter is a professional and easy to use device for accurately measuring air humidity and temperature. Both measured values (%RH and °C or °F) are instantly and simultaneously displayed on the Dual Backlit LCD.

Assessing Indoor Air Quality, Air Conditioning systems, Ventilation and Storage conditions is now only a matter of 'push on the button'.

The micro HM-100 also automatically calculates the Dew Point and Wet Bulb temperature while its Capacitance Sensor easily withstands the effects of condensation and high temperatures, making it perfectly suitable for any HVAC environment.

**The micro HM-100 is supplied with a soft carrying case and 9V battery.**



### Specifications

<b>Power Source:</b>	9V Battery (included)
<b>Display:</b>	4½ Dual Backlit LCD
<b>Measurements:</b>	Humidity, Temperature, Dew Point, Wet-Bulb
<b>Humidity Range:</b>	0% to 100% RH
<b>Humidity Accuracy:</b>	± 2% RH
<b>Temp. Range:</b>	-30°C – 100°C
<b>Temp. Accuracy:</b>	± 0.5 °C
<b>Response Time:</b>	30 Seconds
<b>Sensor Type:</b>	Capacitance
<b>Data Hold:</b>	Yes
<b>MAX/MIN Values</b>	Yes
<b>Auto Power-Off:</b>	Yes, After 15 Minutes (can be disabled)



## micro CL-100 Self-Leveling Cross-Line Laser

The **RIDGID® micro CL-100** offers an amazing value for a cross line laser. With a 'single knob operation' the micro CL-100 is very easy to use and helps you to get your leveling or alignment job done at the blink of an eye!

The micro CL-100 instantly projects a highly visible vertical and horizontal laser line to millimeter accuracy and automatically compensates for misalignments even at slopes of 6°. It can be used at an extended interior range of 30 meters and only needs to be setup once thanks to its integrated 360° swivel base.

The micro CL-100 laser comes packed in a rugged plastic carrying case and includes **laser enhancing glasses** and an **elevating tripod for free!**



38758

£ 85.-

**TRIPOD INCLUDED  
FOR FREE!**



## micro LM-100 Laser Distance Meter

The **RIDGID® micro LM-100** is the ultimate compact Laser Distance Meter that provides quick and accurate distance measurements up to 50 meters. Although small in size, the micro LM-100 is big on features!

Addition, subtraction, area/volume calculation, indirect and continuous measurement are all easily accessible through shortcut keys while results are clearly readable on the bright backlit LCD.

The micro LM-100 also features a protective overmolding, making it perfectly suitable for use in harsh jobsite conditions.

The micro LM-100 is supplied with a soft carrying case and 2x AAA batteries.

36158

£ 85.-



## micro IR-100 Non-Contact Infrared Thermometer

The new **RIDGID® micro IR-100** provides simple, quick, and accurate surface temperature readings (-50°C - 800°C) by simply squeezing the trigger and pointing the ultra-sharp Class II dual lasers at the surface being measured. Results are instantly shown on the backlit Dual LCD.

The 20-to-1 distance-to-spot ratio allows to take measurements from farther and safer distances. Audible and visual high and low alarms instantly alert the user to temperatures outside of the set ranges.

The micro IR-100 also features a tripod thread and **is supplied with a soft carrying case and 9V battery.**

36153

£ 85.-

- INSTANT DETECTION OF GAS LEAKS
- TRI-MODE DETECTION™
- SELF-CALIBRATING & REPLACEABLE SENSOR

36163

£ 85.-

## micro CD-100 Combustible Gas Leak Detector

The **RIDGID® micro CD-100** provides simple and quick readings to quickly identify the presence of combustible gases.

The detector features a flexible 41 cm probe and is designed to detect methane, propane, carbon monoxide, ammonia, hydrogen, natural gas and many other combustible gases at a safe distance.

The micro CD-100 has a rugged ergonomic design and features adjustable sensitivity settings, allowing for quick, precise leak locating even at the lowest levels of gas concentration. The Tri-Mode Detection™ gives the operator the flexibility to be alerted with a visual, audible or vibration alert, adjustable for each environment.

### DISTRIBUTOR

## Full Product Line Ordering Information

Catalog No.	Model No.	Description	Weight (kg)	Std. Pack
37423	micro DM-100	Digital Multimeter	0,38	1
37428	micro CM-100	Digital Clamp Meter	0,30	1
37438	micro HM-100	Temperature Humidity Meter	0,20	1
36153	micro IR-100	Non-Contact Infrared Thermometer	0,30	1
36158	micro LM-100	Laser Distance Meter	0,20	1
36163	micro CD-100	Combustible Gas Leak Detector	0,45	1
38758	micro CL-100	Self-Leveling Cross-Line Laser	0,54	1

**For the complete selection of the Ridge Tool product line, please refer to the Ridge Tool Catalog or [www.RIDGID.eu](http://www.RIDGID.eu).**

\*Prices valid until 31-12-2013. Prices Subject To Change. All prices are excluding VAT.

# RIDGID

Ridge Tool UK  
c/o Emerson Electric UK Ltd  
2nd Floor Accurist House  
44 Baker Street  
London  
W1U 7AL

T: +44 (0) 808 238 9869 UK  
F: +44 (0) 808 238 9904 UK  
T: +353 1 800 936 397 Ireland  
F: +353 1 800 936 240 Ireland  
[ridgid.gb@emerson.com](mailto:ridgid.gb@emerson.com)  
[www.RIDGID.eu](http://www.RIDGID.eu)

  
**EMERSON**  
Commercial & Residential Solutions

RIDGID® operates a policy of continuous improvement and development and reserves the right to change design and specification of our products without notification or alteration of literature.

FY13 62BM\_UK