RIDGID WATER JETTER

KJ-5000 Water Jetter GEN IV

To learn more. contact your RIDGID representative

High quality 60M 3/8" primary hose

2" to 10" (50mm to 250mm) Drain and Sewer Lines

- Powerful 5075 psi actual pump working pressure with a water flow rate of 23 litres per min
- Italian high quality enhanced UDOR pump
- Honda GX690 electric start petrol V-twin engine with anti-vibration protection mounts and an hour meter
- 25L fuel tank with level gauge integrated under the chassis mount
- Primary reel: 60m of quality 3/8" hose
- Remote reel: 60m of quality 1/4" hose
- 4 nozzles in convenient carry box
- Pressure washer lance
- Easy read pressure gauge
- 40L on-board leak free water tank with seamless design
- 3/4" water inlet
- Low level water cut-out sensor for pump protection
- Solid frame construction & powder coat finish with side guard protection
- Easy reach emergency stop button
- Oversized puncture proof wheels
- Tie down/top lift eyelets
- Battery isolator switch
- Hand wash / tank drain facility
- Ute/trailer mounting provision
- Optional 15m whip hose
- Optional Flat bed mounting kit
- Optional foot valve
- Optional swivel nozzle

SPECIFICATIONS

KJ-5000

•	Length	1020mm
•	Width	680mm
•	Height	1390mm

Remote Reel

•	Length	470mm
•	Width	440mm
•	Height	500mm





ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT (kg.)
69478	JETTER, KJ5000 GEN IV RT	185
69483	JETTER, KJ5000 GEN IV W/ FT	193



Nozzle kit



Oversized puncture

proof wheels with nylon bush bearings





RIDGID.COM.AU

CONNECT WITH US

f ridgid australia

RIDGID Tools

ridgid australia



Scan the QR code to request more information or use this web address

www.ridgid.com/au/en/request-demonstration



Ridge Tool (Australia) Pty Ltd ABN 96 008 446 482 • 127 Metrolink Circuit Campbellfield Victoria 3061 Phone 1800 743 443 Fax 1800 801 976 Email ridgid.australia@emerson.com Web www.ridgid.com.au