

FlexShaft™ Machines

High Speed Drain Cleaning

RIDGID

NEW



CLEARs FROM 1¼" TO 4" (32 - 100 mm) DRAIN LINES

RIDGID FlexShaft machines are lightweight, compact and highly efficient machines that deliver wall-to-wall clean in 1¼" to 4" (32 to 100 mm) drain lines up to 70' (21,3 m).

FlexShaft machines can also be operated while an inspection camera is in the line letting you see while you clean. No other soft blockage expert can do that.

- ▶ **WALL-TO-WALL CLEAN**
Chain knockers expand for full pipe cleaning
- ▶ **SIMULTANEOUS CAMERA USE**
FlexShaft machines let you keep your camera in-pipe while you work
- ▶ **INCREASE PRODUCTIVITY**
Faster setup and cleanup, quick cleaning, and cordless convenience for additional time savings
- ▶ **CUSTOMIZE YOUR MACHINE**
A full range of chain knockers and accessories are available

HIGH SPEED DRAIN CLEANING

RIDGID® FlexShaft machines utilize specialized chain knockers attached to a flexible cable that are spun at high speeds by a cordless drill with an adjustable clutch (not included) attached to the center drive shaft. Since the cable spins inside a durable nylon sheath that is housed within a fully contained drum, there is less jobsite mess.



SPECIFICATIONS:

Model	K9-102	K9-204
Drain Capacity	1¼" to 2" (32 - 50 mm)	2" to 4" (50 - 100 mm)
Cable Diameter (without Sheath)	¼" (6 mm)	⅝" (8 mm)
Cable Assy. Diameter (with Sheath)	⅜" (9,5 mm)	½" (12,7 mm)
Cable Assembly Length	50' (15,2 m)	70' (21,3 m)
Rotational Speed	Min. 1800 RPM – Max. 2500 RPM	
Drill Attachment*	⅝" Hex (8 mm)	
Weight (without Drill/Knocker)	24.3 lbs. (11,0 kg)	38.2 lbs. (17,3 kg)
Dimensions (without Drill)	19,2" × 7,5" × 22,1" (488 × 191 × 562 mm)	21,1" × 10,8" × 24,2" (536 × 274 × 615 mm)
Operating temperature	-6°C to 60°C	

* Cordless Drill not included.



CHAIN KNOCKERS

- All pipe types
- For soft blockages and grease



CARBIDE TIPPED CHAIN KNOCKERS

- Hard walled pipes
- For soft blockages, grease, scale and roots

ORDERING INFORMATION:


Catalog No.	Model No.	Description	Weight	
			lb	kg
64268	K9-102 GLOBAL	FlexShaft, 1¼" to 2" (32 - 50 mm) Includes: 50' (15,2 m) of ¼" (6 mm) cable and kit*	29.5	13,4
64278	K9-204 GLOBAL	FlexShaft, 2" to 4" (50 - 100 mm) Includes: 70' (21,3 m) of ⅝" (8 mm) cable and kit**	44.4	20,1

* K9-102 includes: K9-102 1¼" & K9-102 2" Knockers, FlexShaft 4 oz (118 ml) Lubricant, PVC 1¼" & PVC 1½" Attachments, Hex Key 4 mm T-handle Tool, Hex Key 3 mm T-handle Tool, RIDGID Tool Bag, K9-102 & K9-204 Manual Pack.

** K9-204 includes: K9-204 2" & K9-204 4" Knockers, FlexShaft 4 oz (118 ml) Lubricant, Hex Key 4 mm T-handle Tool, Hex Key 3 mm T-handle Tool, RIDGID Tool Bag, K9-102 & K9-204 Manual Pack.

ACCESSORIES:

Catalog No.	Description
64283	FlexShaft Knocker, for 1¼" - 2" (32 - 50 mm) pipe, single chain, carbide tip (use with ¼" (6 mm) cable)
64288	FlexShaft Knocker, for 2" (50 mm) pipe, 2 chain, carbide tip (use with ¼" (6 mm) cable)
64293	FlexShaft Knocker, for 1¼" - 2" (32 - 50 mm) pipe, single chain (use with ¼" (6 mm) cable)
64298	FlexShaft Knocker, for 2" (50 mm) pipe, 2 chain (use with ¼" (6 mm) cable)
64308	FlexShaft Knocker, for 2" (50 mm) pipe, 2 chain, carbide tip (use with ⅝" (8 mm) cable)
64313	FlexShaft Knocker, for 3" (75 mm) pipe, 3 chain, carbide tip (use with ⅝" (8 mm) cable)
64318	FlexShaft Knocker, for 4" (100 mm) pipe, 3 chain, carbide tip (use with ⅝" (8 mm) cable)
64323	FlexShaft Knocker, for 2" (50 mm) pipe, 2 chain (use with ⅝" (8 mm) cable)
64328	FlexShaft Knocker, for 3" (75 mm) pipe, 3 chain (use with ⅝" (8 mm) cable)
64333	FlexShaft Knocker, for 4" (100 mm) pipe, 3 chain (use with ⅝" (8 mm) cable)
64338	RIDGID FlexShaft Lubricant, 8 oz (238 ml)
64343	FlexShaft ¼" (6 mm) Cable Assembly (includes 50' (15.2 m) cable, sheath, couplings)
64348	FlexShaft ⅝" (8 mm) Cable Assembly (includes 70' (21.3m) cable, sheath, couplings)



RIDGID® reserves the right to change design and specification of our products without notification or alteration of literature. For the complete selection of the Ridge Tool product line, please refer to the RIDGID® Tool Catalog or **RIDGID.com**.

© 2019, RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries. All other trademarks belong to their respective holders.

DISTRIBUTOR



For more details visit
RIDGID.com/warranty



Ridge Tool Europe N.V.
Ondernemerslaan 5428
B-3800 Sint-Truiden
Belgium

Tel.: +32 (0)11 598 620
ridgid.eu@emerson.com
RIDGID.com

