

# B-500 TRANSPORTABLE PIPE BEVELLER



# **B-500 TRANSPORTABLE PIPE BEVELLER**







### **CONSISTENCY**

Machined-like finish due to simultaneously working 6 cutters

Accurate bevel angle around the pipe allows one pass beveling

Choice of 3 beveling angles (37,5°, 30°, 45°) to match all welding needs

Adjustable land width from 0" to 3/16" to fit welders' requirements

## **EFFICIENCY**

Fast to set-up and operate. Sets-up and bevels 12" Sch 40 pipe in less than 2 minutes

**Cool to touch,** with pipe ready to handle and weld immediately after beveling

.....

**Easy to use** no matter the skill level; speed LED indicators monitor optimal performance

**Less cleaning,** with no grinding dust & larger chips spread in smaller chip field

# No pre-welding preparation process is going to be faster, cleaner and more accurate than using these RIDGID tools:



### Ordering Information:

Catalog No.	Description	Weight (kg)
49303	Portable Pipe Beveller w/37,5° Cutter Head (230 V, CE)	24
53543	Portable Pipe Beveller w/37,5° Cutter Head (115 V, CE)	24
48863	37,5° Cutter Head w/6 Inserts, 1 Anti-Seize Grease, 8 Screws	1,1
48858	30° Cutter Head w/6 Inserts, 1 Anti-Seize Grease, 8 Screws	1,1
48868	45° Cutter Head w/6 Inserts, 1 Anti-Seize Grease, 8 Screws	1,1
48873	Pack of 6 Inserts, 1 Anti-Seize Grease, 2 Screws, Case	0,1
48883	Anti-Seize Grease – 1 Tube	0,1
48888	Torx Wrench T15/S7	0,1
48893	Spanner Wrench	0,1
48898	5/16 Hex Wrench	0,1

 $49303~\&\,53543$  kits contain: beveller (230 V / 115 V), manual crank handle, 37,5° cutter head, 6-4 edged inserts, torque driver, screws



RIDGID® reserves the right to change design and specification of our products without notification or alteration of literature. For the complete selection of the Ridge Tool product line, please refer to the RIDGID® Tool Catalog or **www.RIDGID.com**.

© 2015, 2015, RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries. All other trademarks belong to their respective holders.

Ridge Tool Europe

3800 Sint-Truiden

Belgium

Schurhovenveld 4820

### Specifications:

- Capacity: 3½" (100 mm) pipe and larger, flat plate; steel & stainless steel
- Pipe Wall/ Plate Thickness: min 0.188" (4,8 mm) / max 0.5" (12,7 mm)
- Bevel Angles: 37.5° (standard, included), 30° & 45° (optional cutter heads)
- Cutter Head: rated for most steel & stainless steel\*
- Land Width: 0-3/16" (4,8 mm) in approximately 1/32" (0,8 mm) increments
- Motor Type: 230 V / 115 V, 50 / 60 Hz, universal
- Operating Speed: 950 RPM (no load)
- Weight: 24 kg
- Size: 40,1 × 29,2 × 33,8 cm (L × W × H)
- Standard Kit: beveller, manual crank handle, 37,5° cutter head, 6-4 edged inserts, torque driver, screws
- \* Application, material, pipe diameter, wall thickness, pipe coatings, operator function, etc. are all key factors that will determine insert life. Beveller cutting head and inserts are optimized for standard A53 mild steel pipe; reduced insert life can be expected on other materials.

#### **DISTRIBUTOR**

