

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014



Version number 3

Revision: 26.02.2014

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *Ridgid Synthetic Threading Fluid, Spray*
- **Article number:** 19611
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Luibricant for Industrial use
Industrielle Verwendung
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
RIDGE TOOL EUROPE
INTERLEUVENLAAN,
RESEARCH PARK
HAASRODE,
3001 LEUVEN
BELGIUM
Tel.: +32 (0) 16380211
Fax: +32 (0) 16380210
- **Further information obtainable from:** Customer Service +32 (0) 16380211 (Office hours)
- **Emergency telephone number:** Customer Service +32 (0) 16380211 (Office hours)

2 Hazards identification

- **Classification of the substance or mixture**
 - **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
 F+; Extremely flammable
R12: Extremely flammable.
 - **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Warning! Pressurized container.
 - **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
-
- **Label elements**
 - **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
 - **Code letter and hazard designation of product:**
 F+ Extremely flammable
 - **Risk phrases:**
12 Extremely flammable.
 - **Safety phrases:**
2 Keep out of the reach of children.
16 Keep away from sources of ignition - No smoking.
51 Use only in well-ventilated areas.
60 This material and its container must be disposed of as hazardous waste.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014

Version number 3

Revision: 26.02.2014



Trade name: Ridgid Synthetic Threading Fluid, Spray

(Contd. of page 1)

- **Special labelling of certain preparations:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
- **Classification in accordance with Directive 75/324/EEC:** Extremely flammable
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane  F+ R12	≤25%
CAS: 39464-70-5	Poly(oxy-1,2-ethanediyl), .alpha.-phenyl-.omega.-hydroxy-, phosphate  Xi R38-41	1-≤2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Wash with water and acidic soap.
- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Rinse out mouth and then drink plenty of water.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** Gastric or intestinal disorders
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, sand, extinguishing powder. Do not use water.
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014

Version number 3

Revision: 26.02.2014

Trade name: *Ridgid Synthetic Threading Fluid, Spray*

(Contd. of page 2)

- Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
 - Do not allow to penetrate the ground/soil.
 - Suppress gases/fumes/haze with water spray.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
 - Dispose of the material collected according to regulations.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Keep away from heat and direct sunlight.
 - Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - Store in cool, dry place in tightly closed receptacles.
 - Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Fumes can combine with air to form an explosive mixture.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Keep container tightly sealed.
 - Do not seal receptacle gas tight.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
- **Specific end use(s)** Thread cutting mediums

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014

Version number 3

Revision: 26.02.2014

Trade name: Ridgid Synthetic Threading Fluid, Spray

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Recommendation: Chemical resistant protective gloves (EN 374)
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

Use safety glasses according to EN 166 : 2001.

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Liquid
Colour:	Red
· Odour:	Odourless
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C
· Flash point:	-97 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	320 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014

Version number 3

Revision: 26.02.2014

Trade name: Ridgid Synthetic Threading Fluid, Spray

(Contd. of page 4)

Upper:	10.9 Vol %
· Vapour pressure at 20 °C:	8300 hPa
· Density at 20 °C:	0.8 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	51.4 %
Water:	18.8 %
VOC (EC)	7.64 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid open flames.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values relevant for classification:
--

106-97-8 butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014

Version number 3

Revision: 26.02.2014

Trade name: Ridgid Synthetic Threading Fluid, Spray



(Contd. of page 5)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

<ul style="list-style-type: none"> · UN-Number · ADR, IMDG, IATA 	<p>1950 UN1950</p>
<ul style="list-style-type: none"> · UN proper shipping name · ADR · IMDG · IATA 	<p>Druckgasverpackung 1950 AEROSOLS AEROSOLS AEROSOLS, flammable</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · ADR 	<div style="text-align: center;">  </div> <p>2 5F Gases.</p>
<ul style="list-style-type: none"> · Class · Label 	<p>2.1 2.1</p>
<ul style="list-style-type: none"> · IMDG, IATA 	<div style="text-align: center;">  </div> <p>2.1 2.1</p>
<ul style="list-style-type: none"> · Packing group · ADR, IMDG, IATA 	<p>Begrenzte Menge LQ2 Void</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p>No</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: 	<p>Warning: Gases. - F-D,S-U</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.02.2014

Version number 3

Revision: 26.02.2014

Trade name: *Ridgid Synthetic Threading Fluid, Spray*

(Contd. of page 6)

· **Transport/Additional information:**

· **ADR**

· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



F+ Extremely flammable

· **Risk phrases:**

12 Extremely flammable.

· **Safety phrases:**

2 Keep out of the reach of children.

16 Keep away from sources of ignition - No smoking.

51 Use only in well-ventilated areas.

60 This material and its container must be disposed of as hazardous waste.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· **Classification in accordance with Directive 75/324/EEC:** Extremely flammable

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

R12 Extremely flammable.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

· **Department issuing MSDS:** Customer Service +32 (0) 16380211 (Office hours)

· * **Data compared to the previous version altered.**