



FlexShaft™ Machines

Clears From 1¼" to 4" Drain Line



For a **FREE DEMONSTRATION***
contact your **RIDGID representative**

*Selected products only & subject to availability & location

RIDGID® FlexShaft machines are lightweight, compact and highly efficient machines that deliver wall-to-wall clean in 1¼" to 4" drain lines up to 70'. FlexShaft machines can also be operated while an inspection camera is in the line, letting you see while you clean. No other soft blockage expert can do that. These upgraded + models have latches around the perimeter to provide easy access to the inside of the machine, an improved cable clamp for increased cable protection, and on-board hex key storage.

- **Wall-To-Wall Clean:** Chain knockers expand for full pipe cleaning
- **Simultaneous Camera Use:** FlexShaft machines let you keep your camera in-pipe while you work
- **Increase Productivity:** Faster setup and cleanup, quick cleaning, and cordless convenience for additional time savings
- **Customize Your Machine:** A full range of chain knockers and accessories are available



RIDGID.COM.AU



CONNECT WITH US

- ridgid australia
- RIDGID Tools
- ridgid_australia

RIDGID® FlexShaft machines utilise specialized chain knockers attached to a flexible cable that are spun at high speeds by a cordless drill attached to the centre drive shaft. Since the cable spins inside a durable nylon sheath that is housed within a fully contained drum, there is less jobsite mess.



SPECIFICATIONS

Model.....	K9-102+	K9-204+
Drain Capacity (Nom.).....	1¼" to 2" (32 – 50 mm)	2" to 4" (50 – 100 mm)
Cable Diameter (without Sheath).....	¼" (6 mm)	⅝" (8mm)
Cable Assy. Diameter (with Sheath).....	⅜" (9,5 mm)	½" (12,7 mm)
Cable Assembly Length.....	50' (15,2 m)	70' (21,3 m)
Rotational Speed.....	Maximum 2500 RPM	Maximum 2500 RPM
Drill Attachment.....	⅝" Hex (8 mm)	⅝" Hex (8 mm)
Weight (without Drill/Knocker).....	24.3 lbs. (11,0 kg)	37.3 lbs. (16,9 kg)
Dimension (without Drill).....	19.2" x 7.5" x 22.1" (49 cm x 19 cm x 56 cm)	21.1" x 10.8" x 24.2" (54 cm x 28 cm x 62 cm)
Operating temperature.....	20°F to 140°F (-6°C to 60°C)	20°F to 140°F (-6°C to 60°C)



RIDGID.COM/FLEXSHAFT

ORDERING INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.) (kg)	
76193	K9-102+	FlexShaft, ¼" - 2" Pipes, Includes: 50' ¼" cable and kit*	29.5	13,4
76198	K9-204+	FlexShaft, 2" - 4" Pipes, Includes: 70' ⅝" cable and kit**	43.5	19,7

* K9-102+ includes: Smooth Chain Knockers, FlexShaft 4oz Lubricant, PVC 1¼" & PVC 1½" Wall Pipe Attachments, Hex Key 4mm, Hex Key 3mm, RIDGID Tool Bag, K9-102+ & K9-204+ Manual Pack, Sheath Stock

** K9-204+ includes: 2" & 4" Smooth Chain Knockers, FlexShaft 4oz Lubricant, Hex Key 4mm, Hex Key 3mm, RIDGID Tool Bag, K9-102+ & K9-204+ Manual Pack, Sheath Stock



Chain Knockers

- All pipe types
- For soft blockages and grease



Carbide Tipped Chain Knockers

- Hard walled pipes
- For soft blockages, grease and scale



Penetrating Head Chain Knockers

- Hard walled pipes
- For wipers, scale, grease and soft blockages

ACCESSORIES

CATALOG NO.	DESCRIPTION	CATALOG NO.	DESCRIPTION
64283	FlexShaft Knocker, ¼" cable, 1¼" - 2" pipe, 1 chain, carbide tip	66578	FlexShaft Knocker, ⅝" cable, 2" pipe, 2 chain, penetrating head
64288	FlexShaft Knocker, ¼" cable, 2" pipe, 2 chain, carbide tip	66583	FlexShaft Knocker, ⅝" cable, 3" pipe, 3 chain, penetrating head
64293	FlexShaft Knocker, ¼" cable, 1¼" - 2" pipe, 1 chain	66588	FlexShaft Knocker, ⅝" cable, 4" pipe, 3 chain, penetrating head
64298	FlexShaft Knocker, ¼" cable, 2" pipe, 2 chain	64338	RIDGID FlexShaft Lubricant, 8oz
64308	FlexShaft Knocker, ⅝" cable, 2" pipe, 2 chain, carbide tip	64343	FlexShaft ¼" Assembly, 50' cable, sheath, couplings
64313	FlexShaft Knocker, ⅝" cable, 3" pipe, 3 chain, carbide tip	64348	FlexShaft ⅝" Assembly, 70' cable, sheath, couplings
64318	FlexShaft Knocker, ⅝" cable, 4" pipe, 3 chain, carbide tip	64363	RIDGID Modified Wallpipe 1¼"
64323	FlexShaft Knocker, ⅝" cable, 2" pipe, 2 chain	64368	RIDGID Modified Wallpipe 1½"
64328	FlexShaft Knocker, ⅝" cable, 3" pipe, 3 chain	64643	FlexShaft ¼" Sheath Stock, 12"
64333	FlexShaft Knocker, ⅝" cable, 4" pipe, 3 chain	64648	FlexShaft ⅝" Sheath Stock, 12"
66568	FlexShaft Knocker, ¼" cable, 1¼" - 1½" pipe, 1 chain, penetrating head	76318	FlexShaft DeadCore ¼" Assembly, 50' cable, sheath, couplings
66573	FlexShaft Knocker, ¼" cable, 1½" - 2" pipe, 2 chain, penetrating head	76328	FlexShaft DeadCore ⅝" Assembly, 70' cable, sheath, couplings

Ridge Tool (Australia) Pty Ltd ABN 96 008 446 482 • 127 Metrolink Circuit Campbellfield Victoria 3061
Phone 1800 743 443 Fax 1800 801 976 Email ridgid.australia@emerson.com Web www.ridgid.com.au

All sales subject to Ridge Tool Company Terms and Conditions of Sales.

All pictures shown are for illustrative purpose only and may not be an exact representation of the product.

R-23-S (623)
Effective Date: April 14, 2024