

K-46 Cordless SinkSnake™



The RIDGID® K-46 Cordless SinkSnake™ clears tough blockages in 3/4" to 3" lines such as sinks, tubs, showers, and urinals. Powered by the RIDGID 18V Advanced Lithium Battery Platform, it provides cordless freedom for professional daily use. Designed with ergonomics and versatility at its core, the K-46 features an integrated, multi-position kickstand for support, a 360-degree rotatable AUTOFEED® that advances and retrieves the cable in forward and reverse rotations, an enclosed rotating drum, and compatibility with different cable sizes and cable tools for unmatched convenience.

- **Ergonomic** Integrated, multi-position kickstand alleviates the weight of the tool in common work environments, such as under cramped sinks and in tubs for improved comfort to reduce user fatigue
- **Versatility** Equipped with the 5/16" x 25' Inner Core Cable but compatible with 1/4" & 3/8" cable diameters up to 50 ft in length, as well as multiple cable tools such as dropheads, spades and c-cutter augers
- Power Features a Brushless DC motor that clears tough blockages in 3/4" to 3" lines such as sinks, tubs, showers and urinals
- **AUTOFEED**® 360-degree rotatable AUTOFEED® advances and retrieves the cable in forward and reverse cable rotations for improved pipe navigation such as tight bends and p-traps
- Design Fully enclosed rotating drum protects plumbing fixtures from accidental damage
- Precision Cable Lock feature improves handling when manually working the blockage
- Optimal Visibility Top-mounted LED light illuminates dark work areas such as underneath sink vanities







Drum Capacity 50' (15.2m) of 1/4" (6mm) Diameter Cable, 50' (15.2m) of 5/16" (8mm)

Diameter Cable 35' (10.7m) of 3/8" (10mm)

Diameter Cable

Power SourceRIDGID® RB-18XX 18V Battery Pack

Motor Type Brushless DC Motor

Voltage18V Amps16 Amps Power 288 W No Load Output Speed0-560 RPM

Maximum AUTOFEED®

Machine Weight w/o Cable

Machine Weight w/ 5/16" x 25' (8mm x 7.6m) IC Cable & 2.5 Ah Battery15.2 lbs. (6.9 kg)

Machine Dimensions (532mm x 222mm x 287mm)

Operating Temperature

Range15°F to 122°F (-10° to 50°C)

Storage Temperature

Range32°F to 113°F (0° to 45°C)

Agency Approval..... cETLus, CE and UKCA standards











Note: Additional Cables & Cable Tools Ordering Information can be found on RIDGID.com.au

ORDERING INFORMATION

	CATALOG NO.	DESCRIPTION
	78078	K-46 Cordless SinkSnake™ C-1IC Cable w/Bulb Auger (5/16"x 25ft) 18V Battery 2.5Ah 18V Charger Gloves
	78048	K-46 Cordless SinkSnake™ C-1IC Cable w/Bulb Auger (5/16"x 25ft) Gloves

ACCESSORIES

CATALOG NO.	DESCRIPTION
78133	K-46 C-6IC Cable Kit — Inner Drum, C-6IC Cable. T-250 Tool Set
78093	K-46 Kickstand
78098	K-46 Carrying Case
78103	K-46 Inner Drum
41937	RIDGID Leather Drain Cleaning Gloves
70032	RIDGID PVC Drain Cleaning Gloves
56513	18V 2.5 Ah Advanced Lithium Battery
56518	18V 5.0 Ah Advanced Lithium Battery
64383	18V Advanced Lithium Battery Charger